

**FAST RECOVERY RECTIFIER**  
**Voltage rang      50 TO 1000 Volts**  
**Current              1.5 Ampere**

**FEATURES**


- \* Fast switching for high efficiency
- \* Glass Passivated Chip junction
- \* Low leakage
- \* High temperature soldering guaranteed  
 260 /10 seconds, 0.375"(9.5 mm) lead length  
 at 5 lbs(2.3kg) tension

**MECHANICAL DATA**

- \* Case : Transfer Molded Plastic
- \* Epoxy: UL94V-O rate flame retardant
- \* Terminals : Plated axial lead, Solderable Per MIL-STD-202  
 Method 208
- \* Polarity : Color band denotes cathode end
- \* Mounting position: Any
- \* Weight : 0.014 ounce. 0.39 gram (approx)

**Plating pb free**

The marking is indicated by part no. with "M".  
 ex: FR151M ~FR157M



**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

- \* Rating at 25 ambient temperature unless otherwise specified
- \* Single phase, half wave. 60Hz, resistive or inductive load.
- \* For capacitive load derate current by 20 %

Characteristic	Symbol	FR151	FR152	FR153	FR154	FR155	FR156	FR157	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	$V_{RRM}$ $V_{RWM}$ $V_R$	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	280	420	560	700	V
Average Rectifier Forward Current Per Leg $T_C=55$	$I_{F(AV)}$	1.5							A
Non-Repetitive Peak Surge Current (Surge applied at rate load conditions halfwave, single phase, 60Hz)	$I_{FSM}$	60							A
Maximum Instantaneous Forward Voltage ( $I_F=1.5$ Amp $T_C=25$ )	$V_F$	1.3							V
Maximum Instantaneous Reverse Current ( Rated DC Voltage, $T_C=25$ ) ( Rated DC Voltage, $T_C=125$ )	$I_R$	5.0 200							uA
Reverse Recovery Time (Note 3)	$T_{rr}$	150			250		500		ns
Typical Junction Capacitance (Note 1)	$C_j$	20							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	50							/W
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-65 to +175							

**NOTES:**

1. Measured at 1.0MHz and applied reverse voltage of 4.0 volts
2. Thermal Resistance from Junction to ambient at .375"(9.5mm)lead length, P.C. board mounted
3. Test conditions:  $I_F=0.5$  A,  $I_R=1.0$  ,  $I_{RR}=0.25$  A

# FR151 Thru FR157

FIG-1 TYPICAL FORWARD CHARACTERISTICS




FIG-3 FORWARD CURRENT DERATING CURVE




FIG-2 TYPICAL REVERSE CHARACTERISTICS




FIG-4 TYPICAL JUNCTION CAPACITANCE







FIG-5 PEAK FORWARD SURGE CURRENT



- Notes:  
 1. Rise Time = 7 ns max. Input Impedance = 1 M  $\Omega$ , 22 pF  
 2. Rise Time = 10 ns max. Input Impedance = 50  $\Omega$



Set time base for 50/100 ns/cm

FIG-6 Reverse Recovery Time Characteristic and Test Circuit Diagram

